

PERFORM 2A

PU PERFORM 2A is a high density underlay made up of 93% natural raw materials and polyurethane binders, laminated with two water vapour control layers.

Height
1 m
(± 1,00 mm)



Content
7 m²



Material

Polyurethane/Mineral 780 kg/m³ (± 10%)

Norma



RWS

Reflected walking sound

24 %

EPLF WD 021029-5



IS

Impact sound reduction

18 dB

DIN EN 10140



R

Thermal resistance

0,009 m² K/W

EN 12664



SD

Protection against moisture

SD100

DIN EN 12086



CS

Compressive strength

220 kPa

DIN EN 826



CC

Compressive creep

48 kPa

DIN EN 1606



DL

Dynamic load

>2.500.000 cycles

DIN EN 13793



RLB

Resistance to large ball

600 mm

DIN EN 13329



PC

Punctual conformability

1,02 mm

CEN TS 16354



RTC

Reaction to fire

B_{fl}

DIN EN13501-1

Application:

High efficient acoustic underlay designed for the installation under laminate and parquet floors. Recommended for underfloor heating system.

Properties

FREE from plasticizers, asbestos, formaldehyde, halogens and heavy metals. It complies with French afsset A+ guidelines on VOC's, the Blue Angel eco label and the German AgBB scheme.

Chemical resistance:

Water, most domestic cleaners, solutions of salt, acids, bases, partly durable against organic solvents and hydrocarbons.

Storage:

Do not store the underlay outdoors, protect it from exposure of sunlight.

Installation:

Easy cutting using an utility or craft knife. Lay the aluminum side up towards the surface covering. Join the subfloor surfaces with the sealing adhesive tape.



ABOVER OÜ
Roosikrantsi tn 2-K300
10119 Tallinn – ESTONIA
VAT EE101813523
info@abover.ee

